




THE Event For The Utility Infrastructure Industry


Underground Construction Technology
International Conference & Exhibition

Failing to Flawless in a Day: How Pre-chlorinated Pipe Bursting Invigorates Arlington Water Utilities Main Replacement Program



City of Arlington & Water Main Background

- Population over 370,000 (50th Largest in USA)
- Daily Water Demands 35 MGD to 115 MGD
- 1,425 miles of public water main
 - 588 miles of asbestos cement (AC) mains
- Average 450 water main breaks annually
 - 2015 – 72% of 533 water main breaks were on AC pipe



Economics of Water Main Failure

- Water main break with small footprint
- 1-4 connections without water service (under 20 psi)
- 6" or smaller potable water main size
- Adequate isolation valve controls
- Less than 5 foot diameter earth disruption
- Response requires 4 crew members, 2 service trucks, 1 mini excavator, 2 megalug adapters, 4 LF of new pipe

- 20 crew hours @ \$20/hr - \$400
- 10 truck hours @ \$75/hr - \$750
- 4 mini excavator hours @ \$100 / hr - \$400
- Sod, fill - \$200
- Mega lug adapters - \$225
- Replacement pipe \$50

TOTAL = \$2,025
Does not include:
Water loss, social
impact, environment
al impact
Cost per LF - \$500!

Economics of Water Main Failure

- Water main break with medium footprint
- ¼ neighborhood 40 connections without water service
- 8"-10" potable water main size
- Substandard isolation valve controls
- 10'-15' diameter earth disruption
- 5'x25' road impact
- Significant time before water could be shut off
- Earth erosion
- Landscape damage
- Water damage to 4-6 town homes
- Significant social and environmental damage

Economics of Water Main Failure

- 10 crew members 20 hours = 200 hrs @ \$20/hr - \$4,000
- 4 service trucks 20 hours = 80 hrs @ \$75/hr = \$6,000
- 1 backhoe 20 hours = 20 hrs @ \$125/hr = \$2,500
- 1 vac truck 6 hours = 6 hours @ \$25/hr = \$750
- 1 loader 10 hours = 10 hours @ \$100/hr = \$1,000
- Water loss 30 min 2,500 GPM – 75,000 gallons = \$300
- Restoration – import backfill, compaction, landscaping, asphalt, curb and gutter - \$22,500
- Water damage to 4-6 town homes - \$15,000

TOTAL = \$52,050

Cost per LF at 15 LF Replaced - \$3,470 Per LF!

Economics of Water Main Failure

- Scientific research completed for large diameter water main failures
- Evaluated social, environmental and economic costs
 - Lost product
 - Repair and return to service
 - Travel delay
 - Supply outage and substitution
 - Health risk
 - Property damage

***"Empirical Analysis of Water-Main Failure Consequences" by Kaylan Piratla**

Economics of Water Main Failure

UCLA Campus, Los Angeles, California – 30 inch steel

- 93 year old steel pipe
- Substandard isolation valve controls – 4 hours!
- Flooded athletic fields, underground garages and various walkways on the University of California in Los Angeles.
- 160 firefighters responded and searched 200 cars
- 75,000 GPM = 48 Million Gallons of water lost
- Significantly increased travel delay due to repair time – 238 hours to repair the 30” steel main!

TOTAL = \$36,100,000

Cost per LF at 75 LF Replaced - \$481,333 per LF!!

Economics of WM Failure - UCLA





Program Overview

- Manage the city's infrastructure assets in the most proactive, efficient way possible
- Replace high maintenance AC water mains
- Utilize Trenchless Technology where feasible
- Utilize in-house design

2016 Pilot: Pre-chlorinated Pipe bursting to replace AC water mains in residential neighborhoods

- 13,125 feet of 6-inch AC replaced with 8-inch HDPE
- Cost effective
- Reduce customer impact
- Utilize HDPE pipe


Fusing & Pre-chlorination of HDPE

- Staging area located away from burst locations to minimize site impact
- Butt fusion is used to connect pipe sections to corresponding burst lengths
- Pressure testing
- Lines capped and disinfected with hypochlorite solution of at least 25 mg/L
- Two consecutive days of samples, taken 24 hours apart




Pipe Bursting Operations 8:00 AM

- Entry and exit pits excavated 4' x 12'
- Service connections pits 3' x 3'
- 8:00 AM – Decommission Main
- Bursting equipment is set in pit and rods are shuttled through host pipe




Pipe Bursting Operations 10:30 AM

- 10:30 AM – Bursting head (or ductile splitter) and expander are attached to the rods which have reached the entry pit
- Pre-chlorinated and sealed HDPE pipe attached to the expander
- Pull back begins



Pipe Bursting Operations Noon

- Rods are removed from the exit pit as pipe is pulled into place
- Noon – New pipe is installed



Pipe Bursting Operations Noon to 3:00 PM

- Noon to 3:00 PM – Connections made
- Ductile Iron fittings, mega lugs, stainless steel inserts, mechanical service saddles



Pipe Bursting Operations 3:00 PM

- 3:00 PM – Post Chlorination Process
- Hypo-chlorus solution sprayed on all connections
- Super-chlorinate new pipeline with slug of chlorine to 300ppm
- 4:00 PM – New main back live







Pipe Bursting Results

- Engineering costs reduced by 94.6% due to following existing utility path and using as-builts
- Construction costs reduced by 36% vs. open cut
- HDPE pipe provides 100 year plus new design life with zero allowance for water loss with fused joints
- Production rate of 300 – 600 feet per day with project completed 44% faster vs. open cut
- Crew visible to each area for one day
- Surgical excavations along project with a reduction in restoration of 87% vs. open cut
- Compact equipment
- Sensitive areas of neighborhoods not impacted
- Zero change orders
- Social costs reduced as intersections remained open, no streets were closed and all residents had full access to homes



THE Event For The Utility Infrastructure Industry

Underground Construction Technology
International Conference & Exhibition

Failing to Flawless in a Day: How Pre-chlorinated Pipe Bursting Invigorates Arlington Water Utilities Main Replacement Program

