


Rehab with Polyurea as SIPP Option



Traditional - Current Application Methodology



Future Deployment Capabilities

(SIPP) Spray-In-Place Pipe

Presenter - *James Baglier*

Pertinent Background:

1. Began developing elastomeric coatings in the early 90's
 - Encasement of asbestos, heavy metals, ect.
2. Performed first polyurea spray application in 1997
3. Began acquiring rehab capability for wastewater systems
 - Manholes, vessels, tanks
 - Plants – various industrial waterproofing
 - Containment , moisture repression
 - Environmental – Brownfields, Landfills
4. 2002 Progressed to developing a concept for Pressure Pipe
 - Worked with, and on various spray tool designs
 - Manufactured & distributed SIPP field rigs




Spray, Seal & Strengthen...

POLYMERIC RESIN
NSF61-5 Structural (ASTM-F1216)



(SIPP) “State of the Art” at conception - Polyurea Pipe Lining Concept:

- First disclosed in 1989
 - AL 8824 Patent Suggestion, Texaco Chemical Company



- Subsequent work in UK in mid 90's
 - Shot independent streams of ISO component and Resin component, mixed on “spinner”

(SIPP) “State of the Art” at conception - Polyurea Pipe Lining Concept:



Early Spray Gun (Video)

Advantages made SIPP Highly Anticipated:

- Polyurea is usually a 1:1 100% solids with no VOC material
- Material is dispensed with plural component spray equipment
- Short gel time & rapid cure allows quick return to service
- Can be formulated with specific desirable physical properties



Sample #2	
Pipe Size:	6" PVC Pipe – 10' long
Tip Size:	#8 Spraying Systems Tip
Nominal Flow Rate:	1.1 gallons/minute
Pull Speed:	21 feet/minute
Estimated coating per pass:	.050"
Number of passes:	4
Measured minimum coating thickness:	.165"
Measured average coating thickness:	.240"
Length of 6" diameter pipe tested:	12"
Cure time before test:	30 days
Nominal burst pressure when tested:	200 psi



Typical Burst Test Results

Advantages made SIPP Highly Anticipated:

- Polyurea is usually a 1:1 100% solids with no VOC material
- Material is dispensed with plural component spray equipment
- Short gel time & rapid cure allows quick return to service
- Can be formulated with specific desirable physical properties



Drill-Tap New Service (Video)



Advantages made SIPP Highly Anticipated:

- Polyurea is usually a 1:1 100% solids with no VOC material
- Material is dispensed with plural component spray equipment
- Short gel time & rapid cure allows quick return to service
- Can be formulated with specific desirable physical properties
- Forms to the host pipe with no annular space
- Accommodates various pipe diameters
- Lateral tie-ins remain clear following application

An ideal solution for:


- Potable Water Mains
- Force Mains
- Transfer Lines
- Myriad of Industrial & Commercial Applications



However, SIPP Lining Has Evolved Little & Grown Slowly:

- Typical installation diagram Circa 1996

- Surface preparation is similar setup
- CCTV's observe real-time installation
- Automatic hose reel controls speed / application film build



Deployment & Technical Issues, Lack of IP - Investment:

- Thorough cleaning of the host pipe is paramount for success
- Suitable temperature, dew point, and air flow is required


Cleaning (Video)



However, SIPP Lining Has Evolved Little & Grown Slowly:

- Typical installation diagram Circa 1996


- Surface preparation is similar setup
- CCTV's observe real-time installation
- Automatic hose reel controls speed / application film build



Deployment & Technical Issues, Lack of IP - Investment:

- Thorough cleaning of the host pipe is paramount for success
- Suitable temperature, dew point, and air flow is required
- Multiple excavations are required to perform work


Slides-Right



However, SIPP Lining Has Evolved Little & Grown Slowly:

- Typical installation diagram Circa 1996


- Surface preparation is similar setup
- CCTV's observe real-time installation
- Automatic hose reel controls speed / application film build



Deployment & Technical Issues, Lack of IP - Investment:

- Thorough cleaning of the host pipe is paramount for success
- Suitable temperature, dew point, and air flow is required
- Multiple excavations are required to perform work
- Winch & reel drawn supply lines can cause ring lines


Slides-Right



However, SIPP Lining Has Evolved Little & Grown Slowly:


- Typical installation diagram Circa 1996

- Surface preparation is similar setup
- CCTV's observe real-time installation
- Automatic hose reel controls speed / application film build



Deployment & Technical Issues, Lack of IP - Investment:


- Thorough cleaning of the host pipe is paramount for success
- Suitable temperature, dew point, and air flow is required
- Multiple excavations are required to perform work
- Winch & reel drawn supply lines can cause ring lines
- Supply lines create friction limiting navigation of elbow fittings
- Only straight pipes are commonly lined



Slides-Right

However, SIPP Lining Has Evolved Little & Grown Slowly:

- Typical installation diagram Circa 1996
 - Surface preparation is similar setup
 - CCTV's observe real-time installation
 - Automatic hose reel controls speed / application film build



The diagram illustrates a cross-section of a pipe installation. A 'Lined Pipe' is being inserted into an 'Unlined Pipe'. The 'Lining Head' is at the front of the lined pipe, connected to a 'Static Mixer' and a 'Hose'. The 'Hose' is connected to an 'Umbilical Hose Drum' which is part of a 'Lining Rig'. An 'Air Compressor' is also connected to the rig. The entire setup is shown in a cross-section view of the pipe being installed.



Deployment & Technical Issues, Lack of IP - Investment:

- Thorough cleaning of the host pipe is paramount for success
- Suitable temperature, dew point, and air flow is required
- Multiple excavations are required to perform work
- Winch & reel drawn supply lines can cause ring lines
- Supply lines create friction limiting navigation of elbow fittings
- Only straight pipes are commonly lined
- **Deployment constraints have limited accelerated growth**

SIPP Lining - Large Pipe

- First Commercial Use – 1995
 - Southern Underground
 - Waste water pipeline
 - Houston, Texas
 - Not a 360° coverage / bottom bare
 - Large diameter / ride-on unit

Video



SIPP Lining - Large Pipe

Robotic Spray-In 2015:

- Ohio Department of Transportation
- 72" Storm Concrete Storm Drain
Cleveland Ohio
- Self Deployed 360° Coverage Structural Liner (750 m)

Video



SIPP Lining Techniques & Tools Are Evolving




First Spin Applicator 1992



Spin Applicator 2012

A History of Materials and Robotic Application

SIPP Lining Techniques & Tools Are Evolving




Optimal Design for Transitioning 90° Ells

3D CAD model of a hydraulic cylinder assembly. Labels include: Hymovip® 13-EP Pressure Sensor (P1, P2), Test Section 30 Hydraulic Cylinder, Seal - Plug Seal - Air Plug, Bore Seal, A.B. (Air Bleed Valve), and Exhaust Gas.


Shadowing Can Result From
Holidays and Thin Coatings
Improper Disk RPM
Result From Poor Resin/ISO
Failure to Reverse Rotation
Blending Pressure Sensors
Improper Resin Blending
On Resin and ISO Circuits
Excessive Travel Speed
Negative Mixture Errors.

Shadowing Can Result From
Holidays and Thin Coatings
Improper Disk RPM
Result From Poor Resin/ISO
Failure to Reverse Rotation
Blending Pressure Sensors
Improper Resin Blending
On Resin and ISO Circuits
Excessive Travel Speed
Negative Mixture Errors.


SIPP Lining - Complicated Pipe Geometries



- 6 Inch Through Unlimited Pipe Sizes



Exxon Mobil Rehab (Singapore)




Con Ed Mock-up March 2015



Launch



Start Lining




CCTV Inspection / Manual Assist around Fittings



To Perform A Successful SIPP Project

1. Establish Host Pipe Condition – Viability to Meet Customer Goals

- A. Substrate material determines applicable cleaning & potential repair methods
- B. Pipe size determines what tools and techniques will be possible
- C. Anticipate potential roadblocks & have contingency procedures identified



To Perform A Successful SIPP Project

1. Establish Host Pipe Condition – Viability to Meet Customer Goals

- A. Substrate material determines applicable cleaning & potential repair methods
- B. Pipe size determines what tools and techniques will be possible
- C. Anticipate potential roadblocks & have contingency procedures identified
- D. Agree up-front on mitigation procedures, implementation triggers, & pricing
- E. Test unproven anticipated procedures and equipment prior to mobilization



To Perform A Successful SIPP Project

1. Establish Host Pipe Condition – Viability to Meet Customer Goals

- A. Substrate material determines applicable cleaning & potential repair methods
- B. Pipe size determines what tools and techniques will be possible
- C. Anticipate potential roadblocks & have contingency procedures identified
- D. Agree up-front on mitigation procedures, implementation triggers, & pricing
- E. Test unproven anticipated procedures and equipment prior to mobilization

2. Surface preparation is paramount to Success

- A. Substrate material and pipe usage determines viable cleaning methods
- B. Cleaning process must fit the circumstances i.e. (water in gas lines “big no no”)
- C. How will undesirable pipe wall contaminants and chemical impurities be negated
- D. Develop containment & debris removal procedures early in the planning stage
- E. Have anticipated procedures pre-approved by resident or consulting engineers

3. Environmental & Ambient Conditions **Must** be Controlled

- A. Internal pipe wall must be dry
- B. Temperature and resulting dew point must be maintained throughout the lining process
- C. Air flow (temp & speed) must be maintained at the tool throughout the length of the pipe


4. Proper Material Selection & QAQC Sign-Off Requirements

- A. Pipe – wall condition, operating pressure, and material conveyed determine selection
- B. Pipe size determines the application thickness per specified service duty
- C. Testing procedures and installation validation should be agreed on in the award phase
- D. Implementation of unproven formulations or application methods should be validated
- E. 3rd party testing and validation

Control Architecture




Tether Drive Capability



Hydrant Cleaning




Inspection / Lining



SIPP / In The Future



Existing Access Capability





NO DIG

1. *Cleaning*
2. *Inspection*
3. *Lining*



Potable Water

END