

PILOT TUBE GUIDED BORING SOLUTIONS

MEET PROJECT CHALLENGES







GUIDED BORING PROJECT CRITERIA





PIPE DIAMETERS

4-48 in. OD pipe with three pass method Up to 120 in. when applied to other technologies



DRIVE LENGTH

Line and grade accuracy up to ¼-in. at 400-lf.+



SMALL FOOTPRINT

GBM systems to fit a minimum 8-ft. shaft to install 1m length pipe for minimized project disruption



GROUND CONDITIONS

Projects with displaceable N Value or SPT = < 50 Non-displaceable N Value > 50 in homogeneous ground with appropriate tooling/equipment



PIPE

Vitrified Clay (VCP), Reinforced Concrete (RCP), Fiber /Glass Reinforced Plastic FRP/GRP, Polymer Concrete, Steel Casing, PVC (with pullback method)



GUIDED BORING APPLICATIONS

Three Pass Method
Guided Auger Boring
Direct Steel Casing Installations
Pilot Tube Rock Drilling
Guided Pipe Ramming
Utility Pullback Installations for HDPE,
PVC, Fiber Optic Cables
Guided Pipe Roofing

GUIDED BORING/PILOT TUBE SYSTEM VERSATILITY OPTIONS



POWER PACKS
HYDRAULIC
POWER
DIESEL OR
ELECTRIC



AUGERS AND CASING




POWERED CUTTER HEADS 20-48-IN



POWERED REAMING HEADS 14-48-IN



MASTER
PUSH RING
DIRECT STEEL
CASING
INSTALLATIONS



SWIVELS FOR HIGH THRUST LOADS




STEEL CASING
ADAPTERS
INCREASE
DIAMETERS IN ONE
OR TWO STAGES



LUBRICATION & FLUSH CUTTINGS




SOFT ROCK TOOLING DRILL BITS




THREE PASS METHOD **STEP 1 PILOT TUBES**






THREE PASS METHOD STEP 2 TEMPORARY CASINGS AND AUGERS






THREE PASS METHOD STEP 3 POWERED CUTTER HEAD





THREE PASS METHOD STEP 3 POWERED REAMING HEAD







THREE PASS INSTALLATION

CASE STUDY

CONTRACTOR D.V.M. UTILITIES

LOCATION ROSEVILLE, MI

OWNER CLINTON TOWNSHIP

PIPE 18-IN VCP, 2M LENGTH

TOTAL LENTH 2,000-FT, 400-FT LONGEST

NO. OF RUNS 12

PROJECT DESCRIPTION/CHAILENGES

- SANITARY SEWER CAPACITY UPGRADE
- 1,000-FT VALUE ENGINEERED TO REDUCE CONSTRUCTION IMPACT IN RIGHT OF WAY
- 13-FT SHAFTS
- UP TO 30-FT DEPTHS
- HARD CLAY GROUND
- POWERED CUTTER HEAD



Underground Construction Technology



THREE PASS INSTALLATION

CASE STUDY

CONTRACTOR MINGER CONSTRUCTION
LOCATION MINNEAPOLIS, MN
OWNER CITY OF MINNEAPOLIS
PIPE 12-30-IN VCP & STEEL CASING
TOTAL LENTH 1,800-FT, 425-FT LONGEST

NO. OF RUNS 9

PROJECT DESCRIPTION/CHAILENGES

- SANITARY SEWER CAPACITY UPGRADE IN DOWNTOWN MINNEAPOLIS
- TWO GUIDED BORING SYSTEMS
- POWERED REAMING AND CUTTER HEADS FOR MULTIPLE DIAMETERS



THREE PASS INSTALLATION

CASE STUDY

CONTRACTOR KRITA ENGINEERING PVT LTD

LOCATION BANGLORE, INDIA

OWNER CITY OF CUTTACK

PIPE DN200-600

TOTAL LENTH 1.86-MI, 187-FT LONGEST


NO. OF RUNS 63

PROJECT DESCRIPTION/CHAILENGES

- SANITARY SEWER ALIGNMENTS IN SAND, CLAY AND HIGH GROUND WATER
- MINIMAL DIAMETER SHAFTS
- EIGHT DIAMETERS OF PIPE
- MULTIPLE POWERED REAMING HEADS



Underground Construction Technology





Underground Construction Technology



GUIDED AUGER BORING ADVANTAGES





IMPROVED ACCURACY

Line and grade accuracy up to ¼-in. at 400-lf.+



LONGER DRIVE POTENTIAL

Much longer lengths are achieved than with an unguided bore



SMALLER CASING SIZES

With an accurate line and grade, smaller casing can be obtained



FASTER INSTALLATION

Productive way to install steel casing



IDEAL FOR MANY GROUND CONDITIONS

Projects with displaceable N Value or SPT = < 50


Non-displaceable N Value > 50 in homogeneous ground with appropriate tooling/equipment




EXPLORATORY WORK

Find obstacles before they find you!


GUIDED AUGER BORING METHOD PILOT TUBE INSTALLATION



GUIDED AUGER BORING METHOD STEEL CASING ADAPTER < 36-IN




GUIDED AUGER BORING METHOD STEEL CASING ADAPTER > 36-IN



GUIDED AUGER BORING STEEL CASING ADAPTERS









SINGLE STAGE

Ideal for non-compacted ground where pipe can be easily advanced with the thrust of the auger boring machine

TWO STAGE


Increase to steel casing diameter in two stages

ARMS FLUSH WITH PIPE ID

Arms allow for the correct positioning of the cutter bit for standard soil removal with augers

GUIDED AUGER BORING WITH SWIVELS









KEEPS PILOT TUBES STATIONARY

ABSORBS ROTATION OF AUGER STRING

HIGH THRUST BEARING



GUIDED AUGER BORING

CASE STUDY

CONTRACTOR JOHN FITHIAN CONTRACTING CO.

LOCATION CECIL COUNTY, MD

OWNER CECIL COUNTY

PIPE 24-IN STEEL CASING

TOTAL LENTH 513-FT, 298-FT LONGEST

NO. OF RUNS 3

PROJECT DESCRIPTION/CHAILENGES

- GRAVITY SEWER UPGRADE AT 0.4% GRADE
- INSTALLATION UNDER STREAM, RAILROAD TRACKS AND ENVIRONMENTALLY SENSITIVE AREA AT DUPONT RESEARCH CENTER



• • •

GUIDED AUGER BORING

CASE STUDY

CONTRACTOR IVY TESTING SERVICE

LOCATION SHREVEPORT, LA

OWNER CITY OF SHREVEPORT

PIPE 16-42-IN STEEL CASING

TOTAL LENTH 4,959-FT, 465-FT LONGEST

NO. OF RUNS 30


PROJECT DESCRIPTION/CHAILENGES

- GRAVITY SEWER UPGRADES
- UNDER SEVERAL HIGHWAYS AND ROADWAYS IN UTILITY LADEN AREA
- DIFFICULT, HIGHLY COMPACTED GROUND CONDITIONS




DIRECT CASING INSTALLATION ALL-IN-ONE SYSTEM


A guided boring direct casing installation uses a high capacity jacking frame to first install pilot tubes then steel casing from a minimal diameter shaft or larger using skid extensions. The jacking frame is equipped with a master push ring or casing adapter to augment the jacking frame torque and manage the soil volume.



DIRECT CASING INSTALLATION USING REAMING HEAD & MASTER PUSH RING




DIRECT CASING INSTALLATION USING SWIVELS



DIRECT CASING INSTALLATION USING MASTER PUSH RING/CASING ADAPTER







CASING ADAPTER TO DISCHARGE SOIL VOLUME

MASTER PUSH RING ADDS ADDITIONAL TORQUE FOR LARGER DIAMETERS AND LONGER DRIVES INSTALL MULTIPLE LENGTHS OF STEEL CASING TO MAXIMIZE PRODUCTION



DIRECT CASING INSTALLATION

CASE STUDY

CONTRACTOR CALGARY TUNNELLING & HORIZONTAL AUGERING LTD

LOCATION CITY OF EDMONTON, AB

OWNER CITY OF EDMONTON

PIPE 16-30-IN STEEL CASING, 1.5M LENGTH

TOTAL LENTH 292-FT


NO. OF RUNS 5


PROJECT DESCRIPTION/CHALLENGES

- INSTALLED GRAVITY SEWER ALIGNMENTS UNDER PEDESTRAIN PATH AT ROGER PLACE
- EDMONTON ARENA DISTRICT PROJECT.
- DEPTHS UP TO 10M
- MANY BURIED UTILITIES




Underground Construction Technology





PILOT TUBE ROCK DRILLING USING DRILL BIT & LUBRICATION





• • •

PILOT TUBE ROCK DRILLING

CASE STUDY

CONTRACTOR INGENIERIA EN TUNELES Y REDES S.A. DE C.V.

LOCATION MONTERREY INT'L AIRPORT, NUEVO LEON, MEXICO

OWNER MONTERREY INT'L AIRPORT

PIPE 36-IN STEEL CASING

TOTAL LENTH 197-FT

NO. OF RUNS 1

PROJECT DESCRIPTION/CHALLENGES

- INSTALLATION TO MEET UTILITY JUNCTION BOX
- CONSTRUCTION UNDER LIVE TAXIWAY
- 5 KSI UCS WEATHERED ROCK



PILOT TUBE ROCK DRILLING

CASE STUDY

CONTRACTOR URBAN CONTRACTORS

LOCATION OKLAHOMA STATE UNIVERSITY CAMPUS

OWNER OKLAHOMA STATE UNIVERSITY

PIPE 12-IN STEEL CASING

TOTAL LENTH 180-FT

NO. OF RUNS 2

PROJECT DESCRIPTION/CHALLENGES

- INSTALLED PARALLEL CHILLED WATER LINES
- INSTALLATION ONE FOOT BELOW SANITARY SEWER LINES
- ALONGSIDE ELECTRICAL DUCT BANK
- RED SHALE GROUND CONDITIONS
- NO DISRUPTION TO CAMPUS LIFE

Underground Construction Technology



PILOT TUBE ROCK DRILLING

CASE STUDY

CONTRACTOR HORIZONTAL BORING & TUNNELING

LOCATION GREELEY, CO

OWNER CITY OF GREELEY

PIPE 36-IN STEEL CASING

TOTAL LENTH 327-FT

NO. OF RUNS 1

PROJECT DESCRIPTION/CHALLENGES

- SANITARY SEWER INSTALLATION
- MIXED-FACE, DENSELY COMPACTED SANDSTONE
- 25-FT DEPTHS
- UNDER HIGHWAY 34



PILOT TUBE ROCK DRILLING

CASE STUDY

CONTRACTOR MACK EXCAVATION

LOCATION HARLEYSVILLE, PA

OWNER PENNSYLVANIA DOT


PIPE 24-IN STEEL CASING

TOTAL LENTH 225-FT

NO. OF RUNS 1

PROJECT DESCRIPTION/CHALLENGES

- UTILITIES CONNECTION FOR HOUSING DEVELOPMENT
- INSTALLED UNDER PENNSYLVANIA TURNPIKE
- RED SHALE UP TO 10 KSI UCS





GUIDED PIPE RAMMING

Guided Pipe Ramming is the method of accurately installing pilot tubes which are followed by steel casing and a pneumatic pipe hammer which transfers force to advance the pipe on line and grade. The method is ideal for a variety of soil conditions and up to large diameters.



GUIDED PIPE RAMMING

CASE STUDY

CONTRACTOR CLAUDE H. NIX CONSTRUCTION

LOCATION DRAPER, UT

OWNER UTAH TRANSIT AUTHORITY

PIPE 20 & 30-IN STEEL CASING

TOTAL LENTH 80-FT


NO. OF RUNS 2

PROJECT DESCRIPTION/CHALLENGES

- INSTALLATION OF UTILITIES ON LINE AND GRADE UNDER ACTIVE COMMUTER RAIL LINES
- WITHIN A FEW INCHES OF RAILWAY'S FIBER OPTIC SIGNAL CONTROL LINES
- 4-HOUR-A-DAY, 20 HOUR TOTAL CONSTRUCTION WINDOW









UTILITY PULLBACK INSTALLATIONS

CASE STUDY

CONTRACTOR CST UTILITIES, LLC

LOCATION HILLARD, OH

OWNER RICH'S FOOD

PIPE 1.5-IN HDPE


TOTAL LENTH 153-FT

NO. OF RUNS 19

PROJECT DESCRIPTION/CHALLENGES

 METHOD USED TO PULLBACK HEATING LINES IN FROZEN FOOD MANUFACTURER'S FLOOR







GUIDED PIPE ROOFING

CASE STUDY

CONTRACTOR TUNNELING SOLUTIONS

LOCATION SYDNEY, AUSTRALIA

OWNER MULTIPLE (3 PROJECTS)

PIPE 12.75-IN STEEL CASING, 20-FT LENGTH


TOTAL LENTH 131-FT AVERAGE

NO. OF RUNS 45

PROJECT DESCRIPTION/CHAILENGES

- METHOD USED TO SUCCESSFULLY INSTALL PILOT TUBES FOR THREE STEEL CASING PIPE ROOFS/CANOPIES
- INSTALLATION IN UP TO 50 MPA GROUND CONDITIONS

Underground Construction Technology



THANK YOU!

CONTACT US

58256 266TH St. Brownsdale, MN 55918 United States

(800) 533.0386

Jason Holden, Director of Sales jholden@akkerman.com

www.akkerman.com

