

E-Power Pipe®: A new trenchless method for underground cable installation

Dr. Gerhard Lang


Jan 31, 2018 - UCT 2018, Track XI

#### **High Voltage Power Grid in Germany.**

- Intention to replace nuclear power plants with renewable energy until 2025.
- Electrical power grid extension to connect the windfarms in the North Sea with the industry in the south. (underground cable priority for DC)
  - North South connections (New DC lines) as underground cables
    - ▶ 1.500 to 2,250km (900 1,600 mi.)
  - Overhead lines use AC technology under special conditions (e.g. distance protected areas), underground lines favor DC.
  - Protests against overhead lines lead to trenchless technology.
  - Commissioning of North-South connections in 2025 (formerly 2022)












#### **Underground Cable Installation.**

Installation methods.


### **Open Trench**



#### **Application**

Shallow installation mostly soft ground Rural area


#### **Semi-Trenchless**



#### **Application**

Shallow installtion
Soft & mixed ground
Rural/less populated area

#### **Trenchless**



#### **Application**

Deep installation
All ground conditions
Urban area/ river crossings





### Conventional Open Cut installation method.

Example Project Raesfeld.

















### **Underground Cable Installation.**

Existing trenchless and semi-trenchless methods.

Pipeline construction







Direct Pipe®




Pipe Express®

Tunnel construction



Pipe Jacking



Segmental Lining

#### Restrictions for cable installation.

by Transition System Operator (TSO).

Limited job site, construction roads, preparation area

No heavy equipment between launch and reception point

Steerable installation of casing pipes for AC & DC lines

Length: 3,300ft – 4.000ft


Depth: 5ft m to 13ft, constant

Diameter casing: ca. DN10" – 16" (250-400mm)

Casing material: plastic, non-conductive, e.g. PEHD

Distance between lines: 3ft constant

Available on market: 2017





# **Comparison Trenchless and Semi-Trenchless Cable Installation Methods.**

# Options & Limits.

	Pipe Express® Semi-trenchless	HDD trenchless	Direct Pipe® trenchless	Pipe Jacking trenchless	Segment Lining trenchless
Diameter [mm]	ID 900-1500	ID 250-1500	ID 711-1500	ID 250-4000	ID 2300-4000
Pipe material	Steel Concrete Plastic (HDPE)	Steel Plastic (HDPE) Cast iron	Steel (Plastic)	Steel Concrete GRP/Hobas Clay pipe	Concrete segments Combisegments (incl. Inliner) Rib & Lagging
Max. drive length *dep. On Ø	40" – 60": 1000m	Ø bis 20": 4km Ø bis 60": 1,7km	Ø bis 38": 300m Ø bis 60": 1,4km	Ø 250mm: 100 m Ø3000mm: 1.5 km	Ø 2000mm: 2 km Ø 3000mm: 8 km
Geology	all Rock up to 100MPa	stable	all Rock up to 150MPa	all	all
Shaft building	Pit	Pit	Pit with bottom plate and sealing	Shaft with bottom plate and sealing	Shaft with bottom plate and sealing
Access	No	No	No	yes > Ø 3000 mm	yes > Ø 3000 mm





# Comparison Trenchless and Semi-Trenchless Cable Installation Methods.

# Options & Limits.

		SEPARATE INSTALLATION ~500mm / 20"			CASING TUNNELS Ø 1,500 mm			CASING TUNNEL Ø 3,000 mm		
		000 000								
Technology:	Ø in mm	Shallow	Accuracy	<b>Length</b> > 1,000 m	Shallow	Accuracy	Length > 1,000 m	Shallow	Accuracy	Length > 1,000 m
› Pipe Jacking	250-4,000									
> Segmental Lining	2,300-4,000									
> HDD	250-1,500									
> Direct Pipe®	700-1,500									
› Pipe Express®	900-1,500									



# Trenchless underground cable construction.

Options & Limits – E-PP meets all requirements.

		SEPARATE INSTALLATION ~500mm / 20"			CASING TUNNELS Ø 1,500 mm			CASING TUNNEL Ø 3,000 mm		
Technology:	Ø in mm	Shallow	Accuracy	Length > 1,000 m	Shallow	Accuracy	Length > 1,000 m	Shallow	Accuracy	Length > 1,000 m
› Pipe Jacking	250-4,000									
> Segmental Lining	2,300-4,000									
> HDD	250-1,500									
> Direct Pipe®	700-1,500									
> Pipe Express®	900-1,500									
13POWER PIPE	250-700									






### Trenchless underground cable construction.


E-POWER PIPE

Machine technology AVNS.



# **AVNS 350 XB**

- **A- Automatische**
- **V- Vortriebsmaschine**
- N- Nass
- S- Strahlpumpe







# Trenchless underground cable installation.

Machine technology AVN<u>S</u>.



















### **NEW Jet Pump Technology.**

Working principle.





Nozzle:

v = 100 m/s (328 ft/s)

p = 50 bar (725 psi)

Mixing chamber

Diffuser:

v = 3.5 m/s (11.5 ft/s)

p = 20 bar (290 psi)





### **NEW Jet Pump Technology.**

First used in conjunctions with the FF Holeopener in HDD.







### Trenchless underground cable installation.

Principle.





# Step 1

Plot Bore to target point with preliminary casing pipes

# Step 2

Disassembly of pipe jacking machine

# Step 3

Mounting of pullhead and product pipe and pullback













# Special installation pipes.


Installation pipes & joint design.

















#### **Demo Movie.**







### Trenchless underground cable installation.



Jobsite setup.





- Current planning: shaft length: ~ 20m | Pilot pipe length: 9m | reduced coupling → high performance
- Adjustable dimensions for pilot pipes, jacking frames and shaft





# Trenchless underground cable construction.



Expected installation performance.

Installation step	1.000m casing installation
Pilot Bore 3,300ft (1.000m)	10 days
Rotation of jacking frame 180° and preparation of pull-in	1 day
Pull-in of casing pipes 3,300ft (1.000m)	3 days   0 days*
Rotation of jacking frame 180° and preparation of pilot Bore	1 day
Total	15 days   12 days*

\* When using a second jacking frame: pull-in and next pilot bore simultaneously possible = 3 days saving





#### Trenchless underground cable installaion.



Development roadmap.

15.12.2016 Product Launch, Schwanau

Equipment in

Machine manufacturing

**July 2016** 

Herrenknecht Plant, Schwanau



November/December 2016

**Test** 

Later

**Measurements** 

Temperature & Magnetic field, IFHT

Herrenknecht Plant, Schwanau





Q2 2017

**Market entry** 

February/March 2017

Pilot project

Amprion; 3 x 300m
















# Tests in Schwanau November 2016.


# E-POWER PIPE

# 6 Test drills.



#### **Test criteria's:**

- Different soil composition, distance, depth
- Construction process
- Cable pull-in + Load monitoring
- Measurement of thermal conductivity over 6 months
- . . .









#### **Tests in Schwanau November 2016.**

Test plant.

























# Product Launch Dec 15th, 2016.

































Amprion - Project Borken

- 3 x 1,00ft (300 m)
- Mostly silt, sand, marl
- Constant depth of 3ft
- Spacing of approx. 30"
- Drilling in February/March 2017












genehmigt oder im Bau realisiert















Pilot Bore.

















Pull-in of HDPE pipe.











#### Overview.

	Drive 1	Drive 2	Drive 3
Pilot Bore			
Duration	36.5h	39h	1
Performance average	600mm/min	800mm/min	800mm/min
Performance max.	1.200mm/min	> 1.200mm/min	> 1.200mm/min
Best daily advance	99m	107m	126m
Pipe handling cycle	40min → 20min	20-25min	20-25min
Pull-in of casing pipe			
Performance max.	1.200mm/min	1.200mm/min	1.200mm/min
Best daily advance	107m	134m	266m
Max. tolerance			
Vertical   horizontal	400mm   500mm	300mm   300mm	*   50mm * Installa depth ch







#### Overview.


















# 2<sup>nd</sup> Project Conneforde Jan. 2018.

Jobsite Images.

- Project: 6 x 270m (890ft) drives
- Installation depth: 2.5-4.5m (8-15ft), curve radius : r=500m (1,640ft)

