

Preparing for electric grid hardening

Brandon Wagner, internal sales manager – Vermeer

Clint Recker, product manager – Vermeer



What's driving the need for reliable and resilient electrical infrastructure?

- Natural disaster — As of October 11, the U.S. has been affected by 15 weather/climate disaster events in 2022 with losses exceeding \$1 billion.
- Shift in energy generation — Renewable energy power plants are on the rise and need to connect to the grid.
- Increasing energy demands — Electric vehicles and construction equipment are trending upwards. Our current electrical infrastructure is not prepared to keep up with this demand and deliver fast-charging options.

<https://www.ncei.noaa.gov/access/billions/>



Natural disaster

- Reduction in impact – the ability to mitigate the size and duration of an outage
- Withstand capability
 - Ability of utility to manage disruptions
- Quick response to restoring service

[https://library.e.abb.com/public/7a64680d31a6477985299cba9612d7c5/9AKK108466A7171_Whitepaper_Grid%20Hardening_v2%20\(Utilities%20have%20options%20when%20it%20comes%20to%20grid%20hardening\).pdf](https://library.e.abb.com/public/7a64680d31a6477985299cba9612d7c5/9AKK108466A7171_Whitepaper_Grid%20Hardening_v2%20(Utilities%20have%20options%20when%20it%20comes%20to%20grid%20hardening).pdf)

Shift in energy generation

- By 2026, global renewable-electricity capacity will rise more than 80 percent from 2020 levels
- Two-thirds coming from wind and solar
 - Increase of 150 percent
- By 2035, renewables will generate 60 percent of the world's electricity.

<https://www.mckinsey.com/industries/electric-power-and-natural-gas/our-insights/renewable-energy-development-in-a-net-zero-world>



Energy demand increases

- Global electricity demand rises by 25 - 30% to 2030 in the Stated Policies Scenario (STEPS) and Announced Pledges Scenario (APS) due to more electric motors, electric vehicles, heat pumps and hydrogen.

<https://www.iea.org/reports/world-energy-outlook-2022/outlook-for-electricity>

Shared responsibility to support the electrical hardening initiative

- Utilities — Going from overhead to underground requires significant upfront costs that are recouped over time because of less ongoing maintenance costs.
- Government — Infrastructure spending (the Infrastructure Investment and Jobs Act) are helping to support the shift to renewable energy sources and its distribution.
- Contractors — Be ready with skilled labor and equipment to underground transmission and distribution lines in rural and urban areas.
- Equipment manufacturers — Outfit the industry with the equipment and technology needed to get the job done.



Government

- California zero emission vehicle regulation
 - Zero-emission vehicle requirements within ACC II are designed for new vehicles to reach 100% zero-emission and clean plug-in hybrid-electric in California by the 2035 model year
- The National Electric Vehicle Infrastructure (NEVI) program will
 - Providing \$5 billion in funding to build out charging infrastructure along highway corridors
 - Filling gaps in rural, disadvantaged, and hard-to-reach locations while instilling public confidence in charging.
- States focusing on hardening in response to severe storms (Texas and Florida)
- Inflation reduction Act- Solar tax credits and a focus on domestic panel manufacturing

<https://www.whitehouse.gov/briefing-room/statements-releases/2022/06/09/fact-sheet-biden-harris-administration-proposes-new-standards-for-national-electric-vehicle-charging-network/>

<https://ww2.arb.ca.gov/our-work/programs/zero-emission-vehicle-program/about>



Utilities

- California Public Utility Commission states converting overhead distribution to underground is up to 10 times more expensive than installing new aerial distribution lines and approximates the cost at \$350 to \$1,150 per foot, or \$1.85 million to \$6.07 million per mile.
- Pacific Gas and Electric Company (PG&E) undergrounded 180 mi (290 km) in 2022, doubling the 2021 completion.
- PG&E is planning to underground 3,600 mi (5,790 km) from 2022 to 2026.

- <https://www.cpuc.ca.gov/industries-and-topics/electrical-energy/infrastructure/electric-reliability/undergrounding-program-description>
- https://www.pge.com/en_US/residential/customer-service/other-services/electric-undergrounding-program/electric-undergrounding-program.page
- https://www.pge.com/pge_global/common/pdfs/customer-service/other-services/electric-undergrounding-program/PGE-Undergrounding-Fact-Sheet.pdf




Manufacturers

- Day 1
 - Introductions and class overview
 - Pretest
 - Soil and drilling fluids
 - HDD overview
 - Pullback and machine maintenance
- Day 2
 - Bore planning
 - DCI®
 - Post test
 - Certificates
 - VR HDD Simulator demo
 - Equipment walkarounds



• Topics

- HDD safety
- Mud mixing
- Calculations
- Drill operation
- Bore planning
- DCI® locating
- DCI® log-while-drilling (LWD™)
- HDD Simulator training
- And more



Installation method considerations

- Considerations
 - Above-ground environment
 - Ground material
 - Bundle size
 - Installation depth
 - Distances
- Open cut — There's a need for deep, wide trenches with specific fill-material requirements.
- Trenchless — In many areas, above-ground obstacles limit how much of the work can be done using open-cut methods or trenchless equipment not capable of installing large product bundles over longer distances.



Long Island Electrical transmission line project

- Long Island, New York
- Sandy soil
- 18,400-ft (5,608.3-m) electrical transmission conduit
- 800 feet between manholes
- Bore diameter: 18 or 20 in (45.7 cm or 50.8 cm)
- Product: double or triple 6-in (15.2-cm) conduit bundles
- Contractor: Eastern Utilities Services LLC and Haugland Group LLC



Equipment

- Vermeer D100x140 S3 HDD
- Vermeer R250C reclaimer
- DigiTrak® Falcon® F5®
- Typical shot length: 800 ft (244 m)



UNDERGROUND
THE UNDERGROUND



Equipment

- Central mud recycling site
- Dirty mud hauled in; clean mud hauled back to drill
- Managed 65,000-gal (246,051.8-L) drilling fluid per day



Project Outcome

- 800 foot bores were being completed in eight hours
 - Pilot: 25 feet per minute
 - Pre-ream: 10 feet per minute
 - Final ream and pipe pullback: 30 feet per minute
- Over one million gallons of drilling fluid use
 - 125 gpm average mud flow rate
 - Drill fluid viscosity greater than 90 seconds
 - Drill returns of 20% to 40% sand content
 - Reclaimer reduced sand content to .35%
 - Clean sand off shaker was used as fill material or for concrete
- 22 drill shots completed in 35 drilling days

Questions?

This presentation contains third-party observations, advice or experiences that do not necessarily reflect the opinions of Vermeer Corporation, its affiliates or its dealers. Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region.

Please contact your local Vermeer dealer for more information on machine specifications.

Vermeer, the Vermeer logo and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. DCI and LWD are trademarks of Digital Control Incorporated.

© 2023 Vermeer Corporation. All Rights Reserved.

UNDERGROUND CONSTRUCTION TECHNOLOGY

THE UNDERGROUND UTILITIES EVENT | February 7-9, 2023 | Orlando, FL

